



TD-30 Series Tunnels

FEATURES

- Digital P.I.D. temperature control
- Automatic cool down circuit
- No maintenance mesh belt
- Adjustable air dampers
- High velocity blower
- Heat ducted to all 4 sides, top and bottom
- Variable speed 0-120 fpm conveyor
- Easy access slide out control panel
- Long life heavy duty Cal rod heaters
- Durable electro-static powder finish
- 16000 – 32000 watts of available heat***
- Emergency stop buttons
- **TWO YEAR WARRANTY**

Model	Max Product Size	Packages Per Minute	Area	Power Required	Machine Size L x W x H	Shipping (Size/Weight) L x W x H
TD-30-12	29" x 11" W x H	60 - 75	30" x 12" x 52" W x H x L	220 Volts 3 PH 60 Amps	60" x 39" x 36"	88" x 48" x 59" 1,025 lbs.
TD-30-19	29" x 18" W x H	60 - 75	30" x 19" x 52" W x H x L	220 Volts 3 PH 70 Amps	60" x 39" x 43"	88" x 48" x 66" 1,075 lbs.
TD-30-26	29" x 25" W x H	60 - 75	30" x 26" x 52" W x H x L	220 Volts 3 PH 70 Amps	60" x 39" x 50"	88" x 48" x 73" 1,125 lbs.

Engineered to Perform. Designed to Endure.

***TD-30-12 -16000 watts of available heat
 ***TD-30-19 – 24000 watts of available heat
 ***TD-30-26 – 32000 watts of available heat



Charles Beseler Company

Packaging Division
 2018 West Main Street
 P.O. Box 431
 Stroudsburg, PA 18360

Toll Free: 800.237.3537
 P: 570.517.0400
 F: 800.966.4515
 Email: customerservice@beseler.com